According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 07.21.2023

Texwipe® Pre-wetted Swabs with 100% Methanol

SECTION 1: Identification

Product Identifier

Product Name: Texwipe® Pre-wetted Swabs with 100% Methanol Product code: TX728

Recommended Use of the Product and Restriction on Use Relevant Identified Uses: For use in various cleaning applications. For industrial use only. Uses Advised Against: Not determined or not applicable. Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States Texwipe, an ITW Company 1210 South Park Drive Kernersville, NC 27284 336-996-7046

Emergency Telephone Number:

United States CHEMTREC 1-800-424-9300 (24 hours) 703-527-3887 (24 hours)

SECTION 2: Hazard(s) Identification

GHS Classification:

Flammable liquids, category 2 Acute toxicity (oral), category 3 Acute toxicity (dermal), category 3 Acute toxicity (inhalation), category 3 Specific target organ toxicity - single exposure, category 1

Label elements

Hazard Pictograms:



Signal Word: Danger

Hazard statements:

H225 Highly flammable liquid and vapor

- H370 Causes damage to organs (Optic nerve, Central Nervous System)
- H301 Toxic if swallowed
- H311 Toxic in contact with skin

H331 Toxic if inhaled

Precautionary Statements:

P210 Keep away from heat, open flames and hot surfaces. No smoking. P233 Keep container tightly closed



Page 1 of 11

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 07.21.2023

Texwipe® Pre-wetted Swabs with 100% Methanol

P240 Ground/bond container and receiving equipment P241 Use explosion-proof electrical, ventilating, and lighting equipment. P242 Use only non-sparking tools P243 Take precautionary measures against static discharge P280 Wear protective gloves, protective clothing, eye protection and face protection. P260 Do not breathe dust, fumes, gas, mist, vapors or spray. P264 Wash hands thoroughly for 15 minutes after handling. P270 Do not eat, drink or smoke when using this product P271 Use only outdoors or in a well-ventilated area P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P370+P378 In case of fire: Use agents recommended in Section 5 to extinguish. P321 Specific treatment (see Sections 4-8 of this SDS and any supplemental information on the product label). P307+P311 If exposed: Call a POISON CENTER or doctor. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor. P330 Rinse mouth P312 Call a POISON CENTER/doctor if you feel unwell P302+P352 IF ON SKIN: Wash with plenty of soap and water P361+P364 Take off immediately all contaminated clothing and wash it before reuse P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P311 Call a POISON CENTER. P403+P235 Store in a well-ventilated place. Keep cool P405 Store locked up P403+P233 Store in a well-ventilated place. Keep container tightly closed

P501 Dispose of contents and container in accordance with local regulations.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 67-56-1	Methanol	>99

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance. This product is toxic by one or more routes of exposure (inhalation, ingestion, skin contact). Take precautions to ensure your own safety before attempting rescue. Wear appropriate safety eyewear, gloves, protective clothing and respiratory protection to prevent exposure. See Section 8 of this SDS for personal protective equipment recommendations. Do not use the mouth to mouth method if victim has ingested or inhaled the product. Give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper device.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 07.21.2023

Texwipe® Pre-wetted Swabs with 100% Methanol

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses, if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Product is highly flammable. Exposure to sources of ignition may cause physical injury.

Causes damage to organs. Effects are dependent on exposure (dose, concentration, contact time). Acute oral exposure may lead to dizziness, drowsiness, headache, breathing difficulties, nausea, vomiting, abdominal pain, and lowering of consciousness. Adverse effects are dependent on exposure (dose, concentration, contact time).

Acute dermal exposure may lead to dizziness, drowsiness, headache, breathing difficulties, nausea, vomiting, abdominal pain, and lowering of consciousness. Adverse effects are dependent on exposure (dose, concentration, contact time).

Acute inhalation exposure may lead to dizziness, drowsiness, headache, breathing difficulties, nausea, vomiting, abdominal pain, and lowering of consciousness. Adverse effects are dependent on exposure (dose, concentration, contact time).

Delayed Symptoms and Effects:

Symptoms of exposure may be delayed.

Immediate Medical Attention and Special Treatment

Specific Treatment:

Skin/eye burns require immediate treatment.

If exhibiting symptoms of exposure, seek prompt medical attention.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Dry chemical, CO2, water spray or alcohol-resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Highly flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 07.21.2023

Texwipe® Pre-wetted Swabs with 100% Methanol

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel and prevent entry. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing with proper techniques in order to prevent contact with skin or eyes. Place contaminated clothing in a sealed container for future disposal.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Toxic if inhaled, toxic if swallowed, toxic in contact with skin. Put on appropriate personal protective equipment, including a self-contained breathing apparatus (see Section 8) before entering area of spill or leak. Avoid breathing dust, mist, fumes, vapors or spray. Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Toxic if inhaled, toxic if swallowed, toxic in contact with skin. Do not handle material unless wearing appropriate personal protective equipment, including respiratory protection (see Section 8). Use only with adequate ventilation. Do not breathe mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Open container slowly to prevent dispersal of material into the air. Prevent contact with skin, eyes and clothing. Handle with caution. Do not handle broken or punctured containers.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight and away from exit paths. Inspect containers and storage area regularly for signs of leak and damage. Store containers at a convenient height for handling, below eye level if possible. High shelving increases the risk of dropping containers, personal injury and exposure. Ensure that appropriate fire fighting and spill-clean up equipment is readily available. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Store separately. Keep container tightly sealed. Store away from

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 07.21.2023

Texwipe® Pre-wetted Swabs with 100% Methanol

incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Methanol	67-56-1	15-Minute STEL: 250 ppm
	Methanol	67-56-1	8-Hour TWA: 200 ppm
NIOSH	Methanol	67-56-1	IDLH: 6000 ppm
	Methanol	67-56-1	15-Minute STEL: 325 mg/m ³ (250 ppm)
	Methanol	67-56-1	REL-TWA: 260 mg/m ³ (200 ppm [up to 10 hr])
OSHA	Methanol	67-56-1	8-Hour TWA-PEL: 260 mg/m ³ (200 ppm)
United States(California)	Methanol	67-56-1	Ceiling Limit: 1000 ppm
	Methanol	67-56-1	15-Minute STEL: 325 mg/m ³ (250 ppm)
	Methanol	67-56-1	8-Hour TWA-PEL: 260 mg/m ³ (200 ppm)

Biological Limit Values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	Methanol	67-56-1	Methanol	Urine	End of shift	15 mg/L

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Use safety glasses with side shields or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 07.21.2023

Texwipe® Pre-wetted Swabs with 100% Methanol

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

AppearanceColorless liquid in solid swabOdorCharacteristicOdor threshold10 ppmpHNot determined or not available.Melting point/freezing point-98°C (-144°F)Initial boiling point/range64.7°C (148.5°F)Flash point (closed cup)9.7°C (49.5°F)Evaporation rate6.3 - Diethyl ether 1.9 - n-butyl acetateFlammability (solid, gas)Not determined or not available.Upper flammability/explosive limit44% (volume)Lower flammability/explosive limit5.5% (volume)Vapor pressure169.27 hPa at 25 °C (77 °F)Vapor density1.11Density0.791 g/mL at 25 °C (77 °F)		Colorloss liquid in colid such
Odor threshold10 ppmpHNot determined or not available.Melting point/freezing point-98°C (-144°F)Initial boiling point/range64.7°C (148.5°F)Flash point (closed cup)9.7°C (49.5°F)Evaporation rate6.3 - Diethyl ether 1.9 - n-butyl acetateFlammability (solid, gas)Not determined or not available.Upper flammability/explosive limit44% (volume)Lower flammability/explosive limit5.5% (volume)Vapor pressure169.27 hPa at 25 °C (77 °F)Vapor density1.11		-
pHNot determined or not available.Melting point/freezing point-98°C (-144°F)Initial boiling point/range64.7°C (148.5°F)Flash point (closed cup)9.7°C (49.5°F)Evaporation rate6.3 - Diethyl ether 1.9 - n-butyl acetateFlammability (solid, gas)Not determined or not available.Upper flammability/explosive limit44% (volume)Lower flammability/explosive limit5.5% (volume)Vapor pressure169.27 hPa at 25 °C (77 °F)Vapor density1.11	C	Characteristic
Melting point/freezing point-98°C (-144°F)Initial boiling point/range64.7°C (148.5°F)Flash point (closed cup)9.7°C (49.5°F)Evaporation rate6.3 - Diethyl ether 1.9 - n-butyl acetateFlammability (solid, gas)Not determined or not available.Upper flammability/explosive limit44% (volume)Lower flammability/explosive limit5.5% (volume)Vapor pressure169.27 hPa at 25 °C (77 °F)Vapor density1.11	shold 1	LO ppm
Initial boiling point/range64.7°C (148.5°F)Flash point (closed cup)9.7°C (49.5°F)Evaporation rate6.3 - Diethyl ether 1.9 - n-butyl acetateFlammability (solid, gas)Not determined or not available.Upper flammability/explosive limit44% (volume)Lower flammability/explosive limit5.5% (volume)Vapor pressure169.27 hPa at 25 °C (77 °F)Vapor density1.11	Ν	Not determined or not available.
Flash point (closed cup)9.7°C (49.5°F)Evaporation rate6.3 - Diethyl ether 1.9 - n-butyl acetateFlammability (solid, gas)Not determined or not available.Upper flammability/explosive limit44% (volume)Lower flammability/explosive limit5.5% (volume)Vapor pressure169.27 hPa at 25 °C (77 °F)Vapor density1.11	oint/freezing point -9	98°C (-144°F)
Evaporation rate6.3 - Diethyl ether 1.9 - n-butyl acetateFlammability (solid, gas)Not determined or not available.Upper flammability/explosive limit44% (volume)Lower flammability/explosive limit5.5% (volume)Vapor pressure169.27 hPa at 25 °C (77 °F)Vapor density1.11	ing point/range 6	54.7°C (148.5°F)
Flammability (solid, gas)Not determined or not available.Upper flammability/explosive limit44% (volume)Lower flammability/explosive limit5.5% (volume)Vapor pressure169.27 hPa at 25 °C (77 °F)Vapor density1.11	it (closed cup) 9	9.7°C (49.5°F)
Upper flammability/explosive limit 44% (volume) Lower flammability/explosive limit 5.5% (volume) Vapor pressure 169.27 hPa at 25 °C (77 °F) Vapor density 1.11	on rate 6	5.3 - Diethyl ether 1.9 - n-butyl acetate
Lower flammability/explosive limit5.5% (volume)Vapor pressure169.27 hPa at 25 °C (77 °F)Vapor density1.11	lity (solid, gas) N	Not determined or not available.
Vapor pressure 169.27 hPa at 25 °C (77 °F) Vapor density 1.11	nmability/explosive limit 4	44% (volume)
Vapor density 1.11	nmability/explosive limit 5	5.5% (volume)
	ssure 1	169.27 hPa at 25 °C (77 °F)
Density 0.791 g/mL at 25 °C (77 °F)	sity 1	1.11
	0	D.791 g/mL at 25 °C (77 °F)
Relative density0.79 - 0.820 °C	ensity 0	0.79 - 0.820 °C
Solubilities 1,000 g/l at 20 °C (68 °F) - completely miscible	s 1	1,000 g/l at 20 °C (68 °F) - completely miscible
Partition coefficient (n-octanol/water) log Pow: -0.77 at 25 °C (77 °F)	coefficient (n-octanol/water)	og Pow: -0.77 at 25 °C (77 °F)
Auto/Self-ignition temperature455.0 °C (851.0 °F) at 1,013 hPa	ignition temperature 4	455.0 °C (851.0 °F) at 1,013 hPa
Decomposition temperature Distillable in an undecomposed state at normal pressure	sition temperature D	Distillable in an undecomposed state at normal pressure
Dynamic viscosity Not determined or not available.	viscosity N	Not determined or not available.
Kinematic viscosity 0.54 - 0.59 mm2/s at 20 °C (68 °F)	viscosity 0	0.54 - 0.59 mm2/s at 20 °C (68 °F)
Explosive properties Not determined or not available.	properties N	Not determined or not available.
Oxidizing properties Not determined or not available.	properties N	Not determined or not available.

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible Materials:

Oxidizing agents.

Hazardous Decomposition Products:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 07.21.2023

Texwipe® Pre-wetted Swabs with 100% Methanol

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment:

Toxic if swallowed Toxic in contact with skin. Toxic if inhaled.

Product Data: No data available.

Substance Data:

Name	Route	Result
Methanol	Oral ATE	LD50 Rat: 100 mg/kg
	Dermal ATE	LD50 Rabbit: 300 mg/kg
	Inhalation ATE	LC50 Rat: 3 mg/L (4 hr [vapor])

Skin Corrosion/Irritation

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Serious Eye Damage/Irritation

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

International Agency for Research on Cancer (IARC): None of the ingredients are listed. **National Toxicology Program (NTP):** None of the ingredients are listed.

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 07.21.2023

Texwipe® Pre-wetted Swabs with 100% Methanol

Specific Target Organ Toxicity (Single Exposure)

Assessment:

Causes damage to organs.

Product Data:

No data available.

Substance Data:

Name	Result
Methanol	Causes damage to Optic nerve (nervus opticus), central nervous system.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

Oral, inhalation, dermal and skin contact.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

Refer to section 4 of this SDS.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:	
Name	Result
Methanol	Fish LC50 Lepomis macrochirus: 15,400 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 18,260 mg/L (96 hr)
	Aquatic Plants EC50 Selenastrum capricornutum: 22,000 mg/L (96 hr [growth rate])

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met. **Product Data:** No data available.

Substance Data:

Name	Result
	Aquatic Invertebrates NOEC Daphnia magna: 122 mg/L (21 d [reproduction])

Persistence and Degradability

Product Data: No data available. Substance Data:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 07.21.2023

Texwipe® Pre-wetted Swabs with 100% Methanol

Name	Result
Methanol	The substance is readily biodegradable. 97% degradation after 20 days, measured by Oxygen consumption.

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
Methanol	This substance does not significantly bioaccumulate in fish. Experimental
	BCFs of < 10 in fish species.

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Methanol	The substance is highly mobile with a very low potential for adsorption to soil and sediment. Koc: 0.13 - 1 dimensionless

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT. **vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:	
Methanol	The substance is not PBT.
vPvB assessment:	•
Methanol	The substance is not vPvB.

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	3175	
UN Proper Shipping Name	Solids containing flammable liquid, N.O.S. (Methanol)	
UN Transport Hazard Class(es)	4.1	
Packing Group	Ш	
Environmental Hazards	None	
Special Precautions for User	None	
Excepted Quantities	E2	
Passenger Air/Rail	15 kg	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 07.21.2023

Cargo Aircraft Only	50 kg
Stowage Category	В
Additional Information	Limited Quantity

International Maritime Dangerous Goods (IMDG)

UN Number	3175	
UN Proper Shipping Name	Solids containing flammable liquid, N.O.S. (Methanol)	
UN Transport Hazard Class(es)	4.1	
Packing Group		
Environmental Hazards	None	
Special Precautions for User	None	
EmS Number	F-A, S-I	
Stowage Category	В	
Excepted Quantities	E2	
Limited Quantity	lkg	
Additional Information	Limited Quantity	

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	3175	
UN Proper Shipping Name	Solids containing flammable liquid, N.O.S. (Methanol)	
UN Transport Hazard Class(es)	4.1	
Packing Group	II	
Environmental Hazards	None	
Special Precautions for User	None	
ERG Code	3L	
Excepted Quantities	E2	
Passenger and Cargo	15 kg	
Cargo Aircraft Only	50 kg	
Limited Quantity	1 kg	
Additional Information	Limited Quantity	

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals:

	67-56-1	Methanol	Listed	
~				

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 07.21.2023

Texwipe® Pre-wetted Swabs with 100% Methanol

67.56.1		Liste d	
67-56-1	Methanol	Listed	5000 lbs
CRA:			
67-56-1	Methanol	Listed	U154
ection 112(r) o	f the Clean Air Act (CAA): None of the ingre	dients are listed.	•
lassachusetts l	Right to Know:		
67-56-1	Methanol		Listed
lew Jersey Righ	t to Know:		
67-56-1	Methanol		Listed
lew York Right	to Know:		
67-56-1	Methanol		Listed
ennsylvania Ri	ght to Know:		
67-56-1	Methanol		Listed
alifornia Propo	sition 65.		

lifornia Proposition 65:

AWARNING: This product can expose you to Methanol; which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial Preparation Date: 07.21.2023

End of Safety Data Sheet

Page 11 of 11